

ASSEMBLY INSTRUCTION LOGAN 2 LIGHT VANITY MODEL NO. LC005667



All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.






You will need 2-Candelabra Base Bulb 40 Watts Recommended 60 Watts Max. USE LED BULBS FOR EXTENDED USE This fixture is Damp Rated

HOW TO INSTALL

- Install the mounting plate to the outlet box using two outlet box screws.
- Install backplate onto the mounting plate, and secure with the screws.
- Install the glass shade and spacer over the socket, then secure with the socket ring by wrench.
- Install the bulb (not included) into the socket.

PART NUMBER


- A. (1)-Mounting hardware
- B. (1)-Mounting plate
- C. (1)-Backplate W4-3/4"xH1"
- D. (2)-Screw
- E. (2)-Sockets
- F. (2)-Glass shade
- G. (2)-Socket ring
- H. (2)-Spacer
- I. (1)-Wrench



D

В

Α



THE FIXTURE CAN BE MOUNTED EITHER UPWARDS OR DOWNWARDS

Н

G

WARNING: This product can expose you to Lead which is known to the state of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov