

DARCY LARGE PENDANT 18"
MODEL NO. LC005783, LC005784, LC005785, LC005786

⚠ WARNINGS AND CAUTIONS

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Please Note:

- 120V input

NOTICE

• The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.

• This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

ASSEMBLY INSTRUCTIONS

1. Remove fixture from its original package.
2. Separate mounting plate (1c) from canopy (2a) by removing canopy screws (2b). Attach mounting plate (1c) to electrical junction box (1a) using junction box screws provided (1e) in hardware package.
3. Place the top shade (3a) on top of ring (3c). Secure suspension rods (2g) to fixture hub (2f) and ring (3c) by threading clockwise. Run wires through top stem (3b), washers (2k), lock nut (2j), center fixture rod (2i) to fixture hub (2f). Attach center fixture rod (2i) to fixture hub (2f), followed by lock nut (2j), washers (2k) and stem (3b) and secure to socket assembly (3d) by threading clockwise.
4. Secure canopy pivot (2c) to canopy (2a) with mounting collar nut (2e). Determine hanging height of fixture by securing rods (2d) to canopy pivot (2c) and fixture hub (2f) after feeding fixture wires through rods.
5. Make proper electrical connections (black to hot "L", white to neutral "N", ground to "GND") with wire nuts (1b) provided in hardware package. Note: the black wire sleeve (2h) that is attached to the fixture wires can be removed after making proper electrical connections, as it is not required to complete installation)
6. Attach canopy (2a) to mounting plate (1c) with canopy screws (2b).
7. Install the recommended lamp (4a) (not provided) (referred on the socket label for maximum wattage and type) to fixture socket.

8. Attach bottom stem (5a) to socket assembly (3d). Secure bottom shade (5b) to ring (3c) with washer (5c) and finial (5d) by threading clockwise.

You are now ready to enjoy your fixture.

