

PIERCE MEDIUM LANTERN PENDANT 17"
MODEL NO. LC005858

⚠ WARNINGS AND CAUTIONS

- Make sure POWER is COMPLETELY OFF at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Please Note:

- 120V input

NOTICE

• The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.

• This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

ASSEMBLY INSTRUCTIONS

1. Remove fixture from its original package.
2. Remove the mounting crossbar (1c) from within the canopy (2a) by loosening the mounting collar nut (2b). Determine the desired length the fixture will hang by selecting from the chain supplied (2d). Remove any unwanted length by opening the last link with chain pliers. Next install the bottom quick link (2e) to the bottom end of the chain and secure the quick link to the fixture body (2f) followed by installing the top quick link to the beginning end of the chain. Weave the fixture wires through the chain assembly (2d), mounting collar nut (2b), canopy (2a), screw collar (1e) and mounting crossbar (1c) and secure the top quick link to the screw collar (1e).
3. Attach mounting crossbar (1c) to junction box (1a), using two junction box screws (1d) (not provided). Cut down the extra wire and connect fixture wires to junction box wires using the marrettes provided (1b). (white to white "N", black to black "L", green to green "G"). Slide canopy (2a) and mounting collar nut (2b) towards ceiling and thread on the mounting collar nut (2b) to the screw collar (1e). This will secure the canopy to the ceiling.
4. Install the recommended lamps (3a) (not provided) (referred on the socket label for maximum wattage and type) to the fixture sockets (3b). *If fixture has integrated LED (Lighting Emitting Diodes) lamp installation is not required*

You are now ready to enjoy your fixture.

