

**PIERCE SEMI-FLUSH 16"**  
**MODEL NO. LC005860**

**⚠ WARNINGS AND CAUTIONS**

- Make sure **POWER** is **COMPLETELY OFF** at the fuse box
- Have your fixture installed by a qualified licensed electrician
- Prepare everything in a clear area
- Wear gloves at all times during this installation
- Read instructions carefully before you start assembly
- Keep this installation sheet for future reference

Please Note:

- 120V input

**NOTICE**

• The important safeguards and instructions outlined in this sheet cannot cover all possible conditions and situations that may occur. It must be understood that caution and certain care factors must be followed. These instructions are provided for your safety and we highly recommend that a licensed, trained electrician install this unit.

• This fixture is designed to be mounted on a correctly installed standard round or octagon box OR through a wiring box with a plaster frame. The box must be securely mounted to the structure of the building. The crossbar and hardware supplied should be used, directly mounting the fixture to the outlet box may make it impossible to correctly align the fixture.

**ASSEMBLY INSTRUCTIONS**

1. Remove fixture from its original package.
2. Remove the mounting plate (1c) from within the canopy (2a) by removing the decorative nuts (2b). Attach the mounting plate (1c) to the junction box (1a) using two junction box screws (not provided) (1d).
3. Connect fixture wires to junction box wires using the marrettes provided (1b) (white to white "N", black to black "L", green to green "G"). Now secure the canopy (2a) to the mounting plate (1c) by aligning the threaded screws (1e) to the holes in the canopy and secure by threading on the decorative nuts (2b).
4. Install the recommended lamps (3a) (referred on the socket label for maximum wattage and type) to the fixture sockets (3b) and restore power. \*If fixture has integrated LED (Light Emitting Diodes) lamp installation is not required\*

You are now ready to enjoy your fixture.

