

ASSEMBLY INSTRUCTION GRACE 9 LIGHT CHANDELIER 22" MODEL NO. LC006340




All electrical components must be installed by a licensed electrician in accordance with the National Electric Code and the appropriate local electrical codes.



You will need 9-Candelabra Base Bulb
40 Watts Recommended 60 Watts Max.



USE LED BULBS FOR EXTENDED USE

This fixture is Dry Rated



Glass Installation Steps

1. Dress ring #1 and ring #2, clockwise, in order of:
(1) Smoke glass, (1) Amber glass, (1) Clear glass and (1) Clear Glass



HOW TO INSTALL

1. Decide the preferred hanging height and choose the correct length of rods needed.
2. Feed the wires through the rods, screw collar ring and canopy (with a bigger center hole). Screw the rods together. Screw one end of the rod assembly onto the top of frame and the other end onto the swivel on the mounting strap.
3. Attach the mounting strap onto the outlet box.
4. Raise the fixture up to the ceiling and do the wire connections. Slip the canopy up along the rods and over the mounting strap. Secure with the screw collar ring.
5. Install the bulb into the socket.
6. Dress the glass as illustrated.

PART NUMBER

- A. (1) - Canopy, D 5 1/8" X H 1"
- B. (1) - Collar ring
- C. (1) - Swivel
- D. (1) - 6" - D16mm - Rod
- E. (3) - 12" D16mm - Rods
- F. (1) - Frame
- G. (18) - Clear glass, D2 3/4 x H7 3/4"
 - i. (9) - Amber glass, D2 3/4 x H7 3/4"
 - ii. (9) - Smoke glass, D2 3/4 x H7 3/4"

WARNING: This product can expose you to Lead which is known to the state of California to cause cancer and/or birth defects or reproductive harm. For more information go to www.P65Warnings.ca.gov